

535,018

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



Rec'd PCT/PTO 12 MAY 2005



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/043679 A1

(51) International Patent Classification⁷: B29C 65/78,
33/20, F03D 1/06

(21) International Application Number:
PCT/DK2003/000777

(22) International Filing Date:
12 November 2003 (12.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2002 01743 12 November 2002 (12.11.2002) DK

(71) Applicant (for all designated States except US): LM
GLASFIBER A/S [DK/DK]; Rolles Møllevvej 1, DK-6640
Lunderskov (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): OLSEN, Søren,
Malcho [DK/DK]; Sønderbyvej 23, DK-6091 Bjert (DK).

JENSEN, Freddie, Reymond [DK/DK]; Hjarupvej 16,
DK-6200 Aabenraa (DK). KLINDT, Peter [DK/DK];
Platanvej 31, Hammelev, DK-6500 Vojens (DK). LIEB-
MANN, Axel [DK/DK]; Høfstrupvej 8, DK-7120 Vejle Ø
(DK).


(74) Agent: CHAS.HUDE A/S; H.C. Andersens Boulevard 33,
DK-1553 Copenhagen V (DK).

(81) Designated States (national): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ,
CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE
(utility model), DE, DK (utility model), DK, DM, DZ, EC,
EE (utility model), EE, EG, ES, FI (utility model), FI, GB,
GD, GE, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR (util-
ity model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK,
SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: MOULD ASSEMBLY WITH CLOSURE MECHANISM



(57) Abstract: Mould assembly including a first mould part (2) and a second mould part (4) for moulding a substantially elongated, closed profile member, in particular a wind turbine blade of fibre-reinforced polymer, said mould assembly including a hinge mechanism (6) with a hinge line (7) extending parallel to the two mould parts in the longitudinal direction of the mould to allow turning of the mould parts in relation to each other between an open position and a closed position. The mould assembly includes displacement means for a rectilinear translational movement of the second mould part (4) between a partially closed position and a completely closed position. The displacement means are formed of guide rods (8) including drive means for displacing the guide rods (8) and thus for moving the two mould parts between the partially closed and completely closed positions. The invention further relates to a method of using the mould assembly.

WO 2004/043679 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.